



Customer Service:
 USA: 800-235-4632
 Canada: 888-275-4397
 International: +1-800-544-6090

HOME

ABOUT US

PRODUCT CATEGORIES

PRODUCT CATALOG

WHERE TO BUY

RESOURCE CENTER

CAREERS

 search

Industrial Products

[Conveyor Belt - Heavyweight](#)
[Conveyor Belt - Lightweight](#)
[Hydraulics](#)
[Industrial Hose](#)
[Power Transmission Products](#)
[Elite Aftermarket](#)
[Trackman Rubber Track](#)
[Transportation - OE Products](#)

Industrial Hose and Fittings



Frontier

[Industrial Hose](#) > [Products](#) > [Air and Multipurpose General Purpose](#) > Frontier
Application:

An economical air and water hose, Frontier is for a wide range of industrial, construction and agricultural applications. Available in 200, 250 and 300 psi working pressures.

Construction:

Tube: EPDM synthetic rubber, RMA Class C (Limited Oil Resistance)

Cover: Black, Red, Yellow, Green or Blue EPDM synthetic rubber

Reinforcement: Spiral synthetic yarn, 2" is braided

Temperature Range: -40°F to 190°F (-40°C to 88°C)

Packaging:

3/16"-3/4" 500' reels, maximum 3 pieces, 50' increments.

1" 450' reels, maximum 3 pieces, 50' increments.

1-1/4" 400' reels, maximum 3 pieces, 50' increments.

1-1/2" 300' reels, maximum 3 pieces, 50' increments.

2" 200', cartons, maximum 3 pieces, 50' increments.

Coupled assemblies available in 1/4", 3/8", 1/2", and 3/4" in red.

Branding: 1/2" Frontier by Continental ContiTech XXX psi WP.

Coupling: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Non-Stock/Sizes: Contact Customer Service for special production run minimum requirements.

Frontier 200 Order Codes: 536-035 (2" black) / 536-040 (2" red) / 569-009 (black) / 569-011 (red) / 569-038 (yellow) / 569-547 (blue)



ID		Nom. OD		Max. WP		Weight	
in.	mm	in.	mm	psi	MPa	lbs./ft.	kg/m
3/16	4.8	0.44	11.2	200	1.38	0.08	0.12
1/4	6.4	0.5	12.7	200	1.38	0.09	0.13
5/16	7.9	0.58	14.7	200	1.38	0.12	0.18
3/8	9.5	0.67	17	200	1.38	0.15	0.22
1/2	12.7	0.81	20.6	200	1.38	0.2	0.3
5/8	15.9	0.97	24.6	200	1.38	0.27	0.4

3/4	19.1	1.12	28.5	200	1.38	0.34	0.51
1	25.4	1.44	36.8	200	1.38	0.54	0.8
1-1/4	31.8	1.73	44	200	1.38	0.75	1.12
1-1/2	38.1	1.98	50.3	200	1.38	0.86	1.28
2	50.8	2.5	63.5	200	1.38	1.16	1.73

Frontier 250 Order Codes: 569-010 (black) / 569-012 (red) / 569-039 (yellow) / 569-506 (green) / 569-548 (blue)

ID		Nom. OD		Max. WP		Weight	
in.	mm	in.	mm	psi	MPa	lbs./ft.	kg/m
1/4	6.4	0.53	13.5	250	1.72	0.11	0.16
5/16	7.9	0.59	15	250	1.72	0.13	0.19
3/8	9.5	0.7	17.8	250	1.72	0.17	0.25
1/2	12.7	0.84	21.3	250	1.72	0.22	0.33
5/8	15.9	0.98	24.9	250	1.72	0.27	0.4
3/4	19.1	1.14	29	250	1.72	0.35	0.52

Frontier 300 Order Codes: 569-516 (yellow) / 569-557 (red) / 569-560 (green)

ID		Nom. OD		Max. WP		Weight	
in.	mm	in.	mm	psi	MPa	lbs./ft.	kg/m
1/4	6.4	0.53	13.5	300	2.07	0.1	0.15
3/8	9.5	0.7	17.8	300	2.07	0.17	0.25
1/2	12.7	0.84	21.3	300	2.07	0.22	0.33
3/4	19.1	1.15	29.2	300	2.07	0.37	0.55
1	25.4	1.48	37.3	300	2.07	0.58	0.86



Registration | Contact Us | Contact Web Master
 CA Prop 65 | Privacy Policy | Terms & Conditions
 Risk Management | ContiTech
FOR DISTRIBUTORS: EPIX USA | EPIX Canada
LOCATIONS: N America | Brazil | Europe | S Africa | Chile | Mexico

ContiTech